

Please delete the last full paragraph on page 4 (page 4, lines 15-23) of the specification and replace it with the following paragraph:

1
a

It is a still further object of this invention to provide a method for reinforcing structural members used to create an architectural structure, including the steps of: providing an extruded hollow beam, preferably made of metal, which beam has at least one reinforcement slat connecting rail or lug integrally connected thereto; providing a reinforcing insert, also preferably made of metal, which has an elongated channel therein adapted to mate in inter-fitting engagement with the connecting rail or lug; slidably placing the reinforcing insert upon the rail or lug, the reinforcing insert being sized and positioned relative to the beam in accordance with engineering calculations which determine the expected distribution of forces along the beam; and assembling a plurality of such beams into an architectural structure.

Please delete the paragraph commencing on page 8, line 20 and ending on page 9, line 4 of the specification, and replace it with the following paragraph:

a2

The invention is also directed to a method for reinforcing structural members used to create an architectural structure, including the steps of: providing an extruded hollow beam, preferably made of metal, which beam has at least one reinforcement slat connecting rail or lug integrally connected thereto; providing a reinforcing insert, also preferably made of metal, which has an elongated channel therein adapted to mate in inter-fitting engagement with the connecting rail or lug; slidably placing the reinforcing insert upon the rail or lug, the reinforcing insert being sized and positioned relative to the beam in accordance with engineering calculations which determine the expected distribution of forces along the beam; and assembling a plurality of such beams into an architectural structure.
